

XGQ型全自动洗脱两用机系列

XGQ automatic eluting dual-purpose machine series

- ★ 电脑控制，全自动，洗涤容量大，洗净率高，能耗低，噪音、振动小，外形美观；
- ★ 结构先进，悬浮减震；
- ★ 变频调速、省电；
- ★ 适用范围广：宾馆、酒店、招待所、医院、洗涤行业、院校等均可使用；
- ★ 棉、毛、麻、化纤织品均可洗涤。

★ Computer control, fully automatic, large washing capacity, high washing rate, low energy consumption, low noise and vibration, beautiful appearance;

★ Advanced structure, suspension and shock absorption;

★ Frequency control, power saving;

★ Wide scope of application: hotels, hotels, guest houses, hospitals, washing industry, colleges, etc. can be used;

★ Cotton, wool, linen and chemical fiber fabrics can be washed.



XGQ120型全自动洗脱机
XGQ120 automatic washing machine



XGQ30型全自动洗脱机
XGQ30 automatic washing machine



XGQ50型全自动洗脱机
XGQ50 automatic washing machine



XGQ100型全自动洗脱机
XGQ100 automatic washing machine

型号 Model	XGQ30F	XGQ50F	XGQ70F	XGQ100F	XGQ120F
处理能力 Handling ability (Kg)	30	50	70	100	120
滚筒尺寸 Roller dim. (mm)	Φ900 × 490	Φ980 × 680	Φ1080 × 720	Φ1200 × 840	Φ1300 × 840
容积 Capacity (L)	305	523	680	950	1162
洗涤转速 Washing speed (rpm)	40	35	33	31	30
均布转速 Uniform speed (rpm)	80	75	70	65	60
中脱 Mid speed (rpm)	420	380	350	310	300
高脱 High speed (rpm)	780	780	680	680	600
电源 Power supply	380V / 50Hz				
电机功率 Motor power (kw)	4	4	5.5	7.5	11
变频器 Inverter (kw)	5.5	7.5	7.5	11	15
加热功率 Heating power (kw)	9	27	27	36	
蒸汽耗比 Steam consumption ratio	0.9kg/kg				
进水管 Inlet pipe	DN25	DN40	DN40	DN50	DN50 × 2
蒸汽管 Steam pipe	DN20	DN20	DN25	DN25	DN25
皂液管 Soap tube	DN15	DN15	DN15	DN15	DN15
外型尺寸 Dimensions (mm)	1300 × 1350 × 1700	1480 × 1800 × 1850	1650 × 1900 × 1900	1750 × 2050 × 1950	1850 × 2050 × 2050
重量 Weight (kg)	850	1800	2500	3000	3500



XGQ25型全自动洗脱机
XGQ25 automatic washing machine

型号 Model	XGQ15F	XGQ20F	XGQ25F
处理能力 Handling ability (Kg)	15	20	25
滚筒尺寸 Roller dim. (mm)	Φ670 × 450	Φ750 × 450	Φ800 × 530
容积 Capacity (L)	149	198	266
洗涤转速 Washing speed (rpm)	50	50	45
均布转速 Uniform speed (rpm)	90	90	80
中脱 Mid speed (rpm)	450	450	420
高脱 High speed (rpm)	780	780	780
电源 Power supply	220V / 50Hz		
电机功率 Motor power (kw)	1.5	2.2	3
变频器 Inverter (kw)	1.5	2.2	3.7
加热功率 Heating power (kw)	6	6	9
进水管 Inlet pipe	DN20	DN20	DN25
蒸汽管 Steam pipe			DN20
皂液管 Soap tube	DN15	DN15	DN15
外型尺寸 Dimensions (mm)	1100 × 1000 × 1580	1100 × 1000 × 1580	1300 × 1350 × 1700
重量 Weight (kg)	600	700	750